



Basic geometry

	S	M	L
Body Height in cm	≤ 175	175 - 186	≥ 186
Seat Height in mm (a)	698 - 828	727 - 857	761 - 891
Seat Tube Length in mm (b)	510	539	573
Top Tube Length in mm (c)	491	518	543
Head Tube Length in mm (d)	63	93	109
Head Tube Angle (e)	73°	73°	73°
Seat Tube Angle (f)	80,5°	80,5°	80,5°
Chainstay Length in mm (g)	420	420	420
Wheel Base in mm (h)	985	1.016	1.051
Stack in mm (i)	469	498	514
Reach in mm (j)	413	435	458
Armpad Stack in mm (m)	542 - 622	570 - 650	604 - 684
Armpad Reach in mm (n)	439 - 493	462 - 516	484 - 538

Component geometry

	S	M	L
Spacer in mm	55,0	55,0	55,0
Stem Length in mm	65	65	65
Handlebar Width in mm	410	410	410
Crank Length in mm	172,5	175	175
Chainring Size	53/39	53/39	53/39
Seat Post Length in mm	350	350	350
Maximum Seat Post Insertion Depth in mm	210	210	210
Minimum Seat Post Insertion Depth in mm	80	80	80
Wheel Size	28"	28"	28"